# Drill**Tech** SSLSA - sub-frame fastener



#### Technical Data Sheet

## **Typical Applications**

- Fastening to aluminium sub-frame within curtain wall applications.
- Fixing aluminium profiles to aluminium substructure.

#### **Product Information**

Size (mm)	Drill Point	Drilling Capacity (mm)	Head Style	Drive	Material	
4.8 x 19	3pt	1.2 - 3.0	Hex	8mm A/F	Stainless Steel	

### Ultimate Pullout Strength, kN

Diameter (mm)	Drill Point	Aluminium 1050 Thickness		
		1.5mm	2.0mm	3.0mm
4.8	3pt	1.0	1.3	2.1

## Ultimate Shear Strength, kN

Diameter (mm)	Drill Point	Aluminium 1050 Thickness	
		1.5mm	3.0mm
4.8	3pt	2.4	3.2

- Pullout tests conducted by VJT Test Laboratory (UKAS Testing 7903) using in-house test method VJTTLSOP14 based on the latest CFA guidance note (method available on request).
- Pullover tests conducted following the principles of BS 5427:2016+A1:2017 (Code of practise for the use of profiled sheet for roof and wall cladding on buildings: Annex E). Tests conducted with 16mm washer fitted under screw head.
- Performance data is unfactored.

All product specifications and data are subject to change without notice.

The data contained in this datasheet is beleived to be accurate and is reproduced in good faith. it is the customer's responsibility to ensure that the product described in this datasheet is suitable for their application.

VJ Technology disclaim any and all liability for any errors, inaccuracies or incompleteness contained in the datasheet. In addition VJ Technology makes no warranty, representation or guarantee regarding the suitability of the product described by the datasheet for any particular or associated purchase. V4 | SIN | DT | SSLSA |



#### Features & Benefits

- Drills 1.2-3mm thick aluminium
- A2 (304) stainless steel
- Coarse thread
- Unwashered

### Installation Tips

- For optimal Install use a screwgun with depth setting nosepiece and RPM range of 1500-2200
- Avoid overdriving/ overtightening
- Fastener is fully seated when head is in contact with material surface
- A minimum of 3 threads must protrude through the rear of the metal structure

VJ Technology Limited Technology House, Brunswick Road, Cobbs Wood Industrial Estate, Ashford, Kent. TN23 1EN t.01233 637695 e. enquiries@vjtechnology.com www.vjtechnology.com