# Technical Data Sheet

28/03/2018 Issue 1

## **Contents**

- 1. Supplier
- 2. Product Description
- 3. Directions for Use
- 4. Storage
- 5. Disclaimer

### **Features**

- Lubricates
- Penetrates
- Protects

# Aerosol Solutions Silicone Spray 500ml

### **Supplier**

Aerosol Solutions Ltd Unit C2 Bridgefield Industrial Estate Draycott Road Breaston Derby DE72 3DS

T: 01332 870 030 F: 01332 870 033

E: accounts@aerosolsolutions.co.uk

# **Product Description**

**Aerosol Solutions Silicone** is a clear, non-staining silicone based lubricant that is suitable for use in a wide range of industrial and domestic applications. Due to the cleaning and lubricating properties of silicone, **Silicone Spray** finds uses in the furniture, textiles, construction, bed manufacturing and many other industries, as well as the following;

- On machinery and moving parts, seized locks, squeaking hinges, sticking draws, metal clothing zips, tools, cutting blades or anywhere that a fine lubricating film is required.
- 2. As a protective film to inhibit the build-up of dust, fluff and foreign matter on machinery and moving parts.
- 3. To give a protective water repelling coating to, clothing, tents, golf bags, umbrellas, fishing and camping equipment and other similar items, making them rain and shower proof.
- 4. **Silicone Spray** can be used as a general purpose polish on car interiors and door panels.

**Silicone Spray** is colourless with a faint odour and is safe on most surfaces such as metal, plastic, rubber, wood and paintwork. However it is always recommended that a small sample of the materials are tested first, to ensure the suitability of the product for the application

# Technical Data Sheet

28/03/2018 Issue 1

### **Directions for Use**

#### USE IN A WELL VENTILATED AREA

Dependent upon application, **Silicone Spray** should be sprayed onto the surface from 15cm (6 inches) to 25cm (10 inches). If required, buff with a clean cloth.

### **Storage**

Protect from extremes of temperature in a controlled environment between 15 and 35°C, and away from direct sunlight. Stored under the correct conditions, in original, unopened containers, the product will have a shelf life of 12 months.

#### DO NOT ALLOW THE PRODUCT TO FREEZE

### Disclaimer

All the information in the Data Sheet is based on practical experience and is published in good faith. However, because we have no control over the manner or conditions in which our products are used, or over work undertaken or end product manufactured by the purchaser, we cannot accept liability for results. Responsibility for ascertaining the suitability of products for his purposes rests with the purchaser. All conditions, representations, statements, warranties or guarantees whatsoever, whether express, implied or statutory, in respect of any goods manufactured, sold or supplied by us are hereby expressly excluded and we accept no liability in respect of any claim for damage or consequential loss caused to any property arising directly or indirectly out of the use of our products or goods.