




Teks® - TC25, TC50, TC62, TC75 & TC100

Self drilling fasteners for general components to steel



8mm Hex



Applications

- Steel framing systems
- Brick Ties
- Bracketry to steel
- Cladding and roofing applications
- Composite panels
- Wind posts
- Composite steel decking
- General metal construction

Installation Guidelines

- A standard screwgun with a depth sensitive nosepiece should be used to install Teks. For optimal fastener performance, the screwgun should be a minimum of 6 amps and have an RPM range of 0-2500.
- Adjust the screwgun nosepiece to properly seat the fastener.
- New magnetic sockets must be correctly set before use. Remove chip build-up as needed
- The fastener is fully seated when the head is flush with the work surface
- Overdriving may result in torsional failure of the fastener or stripout of the substrate
- The fastener must penetrate beyond the metal structure a minimum of 3 pitches of thread

Teks®, Climaseal® and Spex™ are trademarks of ITW Buildex and Illinois Tool Works, Inc.

→ TC Teks, the original self-drilling self-tapping fastener for fixing into steel section of 0.9mm - 5.0mm

Technical Data for 8mm Hex Head

SCREW TYPE	Total length	Diameter	Steel Thickness	Maximum Fixture Thickness*	Eurocode
TC25	25mm	5.5mm	0.9mm - 5.0mm	13mm	920028
TC50	50mm	5.5mm	0.9mm - 5.0mm	36mm	920126
TC62	62mm	5.5mm	0.9mm - 5.0mm	50mm	920127
TC75	75mm	5.5mm	0.9mm - 5.0mm	62mm	920199
TC100	100mm	5.5mm	0.9mm - 5.0mm	87mm	920125

*Please note - fixture may require pre-drilling in some applications

Performance Data

Recommended Tensile Values

Steel Thickness							
0.9mm	1.2mm	1.5mm	2mm	2.5mm	3mm	4mm	5mm
0.5kN	0.8kN	1.11kN	1.56kN	2.39kN	2.88kN	3.34kN	4.3kN

Recommended Shear Values

Steel Thickness							
0.9mm	1.2mm	1.5mm	2mm	2.5mm	3mm	4mm	5mm
1.14kN	2.0kN	2.38kN	2.89kN	2.91kN	2.91kN	2.91kN	2.91kN

Ultimate Fastener Loads

TENSILE	SHEAR	TIGHTENING TORQUE
12.6kN	9.09kN	≤ 10Nm

Typical Performance Parameters

Climaseal® Coating

- Climaseal is a high quality metal filled thermoset coating. Climaseal has been uniquely formulated to react and form a complete long life protection to provide the optimum in corrosion resistance properties. Climaseal is self sacrificing to the base substrate if penetrated or damaged. Fasteners coated with Climaseal exhibit excellent resistance most forms of abrasion and torque.
- **Chemical Identification:** Organometallic Polymer
- **Colour:** Silver/Metallic Grey
- **Cure:** Thermoset
- **Typical Film Properties:**
 - Humidity Resistance: Excellent
 - Solvent Resistance: Excellent
 - Impact Resistance: Excellent
 - UV Resistance: Excellent
- **Fastener:** TEKS
- **Base Treatment:** Zinc (non-electrolytically applied)
- **Film:** Climaseal (Thermoset Polyester)
- **Test Method:** Salt Spray, ASTM B117 - 720 hrs
Kesternich, DIN50018, 2.0L