

1340 - ITW Spit Tapcon

Description

The original masonry fastening system that cuts it's own thread into concrete, brick and hollow block. Tapcon® features a Hi-Lo® thread design for superior pull-out resistance, and the application of Climaseal® coating adds extra corrosion resistance.



Advantages

- Fast installation, Drill, Drive, Done
- Available in M5 and M6 and in lengths from 32 - 125mm
- Every box includes a free 'close tolerance' masonry bit
- Removable - adjustable
- Can be installed close to edges
- Slotted Hex and Phillips flat head styles give flexibility in applications
- Excellent corrosion protection
- Fire resistant

Typical applications

- Conduit clips
- Cable trays
- Channel
- Suspended ceilings
- Timber base plates
- Timber battens
- Hand rails
- Signs



Installation procedure



Product Range

VJT Code	Description	Screw Ø	Drive Style	Drill-Ø (mm)	Fixture Th'ness (mm)	Min. Drill Depth (mm)	Min. Embed. Depth (mm)	Overall Length (mm)	Box Qty
13400010	Tapcon 3F32 4.8 x 32 Csk - 921507	5mm	P2	4	0 - 7	35	25	32	100
13400020	Tapcon 3F45 4.8 x 45 Csk - 921508	5mm	P2	4	5 - 20	35	25	45	100
13400030	Tapcon 3F57 4.8 x 57 Csk - 921509	5mm	P2	4	17 - 32	35	25	57	100
13400040	Tapcon 3F70 4.8 x 70 Csk - 921510	5mm	P2	4	30 - 45	35	25	70	100
13400050	Tapcon 3F82 4.8 x 82 Csk - 921511	5mm	P2	4	42 - 57	35	25	82	100
13400060	Tapcon 3F100 4.8 x 100 Csk - 921512	5mm	P2	4	60 - 75	35	25	100	100
13400070	Tapcon 4F32 6.3 x 32 Csk - 921513	6mm	P3	5	0 - 7	35	25	32	100
13400080	Tapcon 4F45 6.3 x 45 Csk - 921514	6mm	P3	5	5 - 20	35	25	45	100
13400090	Tapcon 4F57 6.3 x 57 Csk - 921515	6mm	P3	5	17 - 32	35	25	57	100
13400100	Tapcon 4F70 6.3 x 70 Csk - 921516	6mm	P3	5	30 - 45	35	25	70	100
13400110	Tapcon 4F82 6.3 x 82 Csk - 921517	6mm	P3	5	42 - 57	35	25	82	100
13400120	Tapcon 4F100 6.3 x 100 Csk - 921518	6mm	P3	5	60 - 75	35	25	100	100
13400130	Tapcon 4F125 6.3 x 125 Csk - 921519	6mm	P3	5	85 - 100	35	25	125	100
13400140	Tapcon 3H32 4.8 x 32 Hex - 921498	5mm	6.5mm Hex	4	0 - 7	35	25	32	100
13400150	Tapcon 3H45 4.8 x 45 Hex - 921499	5mm	6.5mm Hex	4	5 - 20	35	25	45	100
13400160	Tapcon 3H57 4.8 x 57 Hex - 921500	5mm	6.5mm Hex	4	17 - 32	35	25	57	100
13400170	Tapcon 4H32 6.3 x 32 Hex - 921501	6mm	8mm Hex	5	0 - 7	35	25	32	100
13400180	Tapcon 4H45 6.3 x 45 Hex - 921502	6mm	8mm Hex	5	5 - 20	35	25	45	100
13400190	Tapcon 4H57 6.3 x 57 Hex - 921503	6mm	8mm Hex	5	17 - 32	35	25	57	100
13400200	Tapcon 4H70 6.3 x 70 Hex - 921504	6mm	8mm Hex	5	30 - 45	35	25	70	100
13400210	Tapcon 4H82 6.3 x 82 Hex - 921505	6mm	8mm Hex	5	42 - 57	35	25	82	100
13400220	Tapcon 4H100 6.3 x 100 Hex - 921506	6mm	8mm Hex	5	60 - 75	35	25	100	100
13400230	Tapcon 4H125 6.3 x 125 Hex	6mm	8mm Hex	5	85-100	35	25	125	100

Tapcon range Stainless Steel

VJT Code	Description	Screw Ø	Drive Style	Drill-Ø (mm)	Fixture Th'ness (mm)	Min. Drill Depth (mm)	Min. Embed. Depth (mm)	Overall Length (mm)	Box Qty
13440010	Tapcon 4H32 1/4" x 1 1/4" 410 Hex	6mm	8mm Hex	5	0 - 7	35	25	32	100
13440020	Tapcon 4H45 1/4" x 1 3/4" 410 Hex	6mm	8mm Hex	5	4 - 20	35	25	45	100
13440030	Tapcon 4H57 1/4" x 2 1/4" 410 Hex	6mm	8mm Hex	5	17 - 32	35	25	57	100
13440040	Tapcon 4H70 1/4" x 2 3/4" 410 Hex	6mm	8mm Hex	5	30 - 45	35	25	70	100