



Never compromise on quality!



LINE-IT LINEMARKER PAINT

High Performance Line Marking Paint



BUILDERS COMPLETE RANGE

Description:

A xylene and lead free, high performance, fast drying resin based permanent line marking paint in a range of colours. CFC Free.

Uses

Suitable for interior and exterior use (e.g. car parks, tennis courts, gymnasia) on wood composites, concrete, tarmacadam, gravel and grass. **LINE-IT PAINT** is ideal for survey marking and when correctly applied produces a fast drying, hard wearing line. Non-clogging formulation and nozzle. Excellent UV colour stability.

Preparation

Ensure all surfaces are clean, dry and free from grease or oil or any other contaminants that may hinder adhesion.

Application

For best results use in conjunction with a marking applicator.

Shake the can for at least 1 minute after the agitator balls are heard rattling. Shake frequently during use. After use clear the valve ready for storage by spraying in an upright position for 1-2 seconds ensuring the nozzle is pointing AWAY from people and surfaces. Remove nozzle and store vertical. If the can is to be stored for longer than 1 month the can should be stored horizontal.

In windy conditions care must be taken to avoid overspray.

Drying Time

Bond It **LINE-IT PAINT** is fast drying. Drying times are dependent on the temperature at which it is applied, for best results the temperature should be above 10°C.

Normally **LINE-IT PAINT** should be touch dry and ready to receive light traffic after 30 minutes. For heavy traffic leave for 2 hours. Drying times are dependant on temperature and the moisture content of the substrate.

Cleaning

Use Bond It uPVC SOLVENT CLEANER to clean any tools or spillages/ over spray.

Coverage

One 750ml can will yield a line of 60m to 100m (200 to 350ft) of 50mm (2") width, depending on application weight.



Container Size

750ml aerosol tins.

Colour

LINE-IT PAINT comes in 7 colours: yellow, white, red, blue, green, orange and black.

Shelf Life

48 months from date of manufacture when stored in unopened tins.

Storage Conditions

Store in cool, dry conditions away from heat and out of direct sunlight. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations. Do not pierce or burn canister after use.

Spilt material should be mopped up immediately with an absorbent cloth and a suitable solvent cleaner.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Physical Form	Opaque viscous liquid
Flash Point	Less than -40°C
Solubility in Water	Immiscible
UFI	KU50-R0MG-PO0M-13KW



Product Details:

Colour:	Yellow	White	Red	Blue
Code:	BDLM001	BDLM002	BDLM003	BDLM004
Size:	750ml	750ml	750ml	750ml
Barcode:	5060021362551	5060021362568	5060021362575	5060021362834
Colour:	Green	Orange	Black	
Code:	BDLM005	BDLM006	BDLM007	
Size:	750ml	750ml	750ml	
Barcode:	5060021364142	5060021361459	5060021364166	



Part of the Bond It Builders Complete Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001
ISO 14001; ISO 45001



BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V5 20/05/20
Supersedes: V4 25/07/20