

# Aquafix

Revision: 21/03/2015

Page 1 from 1

## Technical data

Basis	styrene acrylate
Consistency	Paste
Curing system	Physical drying
Skin formation* (20°C / 65% R.H.)	Ca. 10 min
Density	Ca. 0,95 g/ml
Maximum allowed distortion	10 %
Temperature resistance	-20 °C → 90 °C
Application temperature	5 °C → 30 °C
Shrinkage	Ca. 20%

(\*) these values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

## Product description

Aquafix

## Properties

- Totally transparent, crystal clear
- Very easy to apply
- Solvent based
- Good adhesion to many substrates
- Can be painted over after curing
- UV resistant, waterproof and resistant to weathering

## Applications

- Repair product for leaks in gutters, drainpipes.
- Implementing emergency repairs, even in rain.
- Sealant at cracks and seams.
- Joints with movement till max. 10%

## Packaging

*Colour:* transparent

*Packaging:* 310 ml cartridge

## Shelf life

At least 12 months in unopened packaging in a dry storage place at temperatures between +5°C and +25°C.

## Substrates

*Substrates:* all usual building substrates

*Nature:* clean, free of dust and grease, can be moist.

*Surface preparation:* No pretreatment required  
We recommend a preliminary adhesion test on every surface.

## Application method

*Application method:* With manual- or pneumatic caulking gun. Finish with spatula or filling knife.

*Cleaning:* Clean with white spirit or Surface Cleaner immediately after use.

*Finishing:* With a soapy solution or Soudal Finishing Solution before skinning.

*Repair:* With the same material

## Health- and Safety Recommendations

Take the usual labour hygiene into account.  
Consult the packaging label for more information.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions beyond our control, no liability under this publication are accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.