

Application guidelines for Carpet film

Carpet Protection Film for Synthetic Carpets Only - Do Not Apply to Wool Carpets or Rugs –

The film will adhere to itself; you can create wider strips if desired.

Various ambient and traffic conditions will affect the films performance. In all cases do not allow the film to remain on carpet for **longer than 30 days**. If necessary, remove old film and replace immediately with fresh film.

Film is one time use only, remove and dispose of at the end of the project in accordance with environmental regulations.

Do not apply carpet protection film to hard surfaces, such as hardwood, ceramic tile, linoleum or marble.

PLEASE DO NOT APPLY FILM IF CARPET OR SURFACE IS DAMP.

Damp carpet or underlay and uncured concrete cause conditions of rising moisture vapour.

Rising moisture that is prevented from escaping may cause discolouration of carpet fibres. Concrete floors, even with adequate curing time, can present unacceptable moisture conditions due to excessive amount of moisture vapour passing through to the surface.

DO NOT APPLY FILM OVER NEWLY LAID CARPETS WHERE ADHESIVE HAS BEEN USED.

The areas should be ventilated for 48 to 72 hours to allow any residual vapours from glue, carpet or underlay to dissipate.

Usually high traffic areas (show houses) may require renewal of film every 15 days

CUSTOMERS MUST FULLY EVALUATE THE PRODUCT BY TESTING PRIOR TO USING. It suggested that the film should be checked regularly for adhesive residue as carpets can have chemicals designed to protect that are affected by the adhesive

In the event of any adhesive residue being left behind we recommend professional carpet cleaning only.