

Printing date 29.06.2017 Version number 4 Revision: 27.06.2017

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: TREMCO AW421

· MSDS code: W-T-AW421

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Cleaner solvent

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410

msds@tremco-illbruck.com

### · Further information obtainable from:

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.tremco-illbruck.co.uk, uk.info@tremco-illbruck.com

## · 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times please contact your national poisoning centre.

## **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

#### · 2.2 Label elements

## · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Contains:

toluene

(Contd. on page 2)



Printing date 29.06.2017 Version number 4 Revision: 27.06.2017

**Trade name: TREMCO AW421** 

(Contd. of page 1)

#### butanone

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

## · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P313 Get medical advice/attention.

## · Supplemental information:

Restricted to professional users.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Solvent mixture

· Dangerous components:			
CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51-xxxx	toluene Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	75- <100%	
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	20- <30%	

## Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons ≥15-<30%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information:

Take affected persons out of danger area and lay down.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)



Printing date 29.06.2017 Version number 4 Revision: 27.06.2017

**Trade name: TREMCO AW421** 

(Contd. of page 2)

### · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

## · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

## · After swallowing:

IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

Seek immediate medical advice.

## · 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty

Headache

**Dizziness** 

Nausea

Harmful: may cause lung damage if swallowed.

Chemical pneumonia.

May cause damage to organs through prolonged or repeated exposure.

Irritating to eyes and skin.

- · Information for doctor: No further relevant information available.
- · Hazards No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO)

Carbon dioxide

Hydrogen chloride (HCI)

Nitrogen oxides (NOx)

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

GE



Printing date 29.06.2017 Version number 4 Revision: 27.06.2017

**Trade name: TREMCO AW421** 

(Contd. of page 3)

### **SECTION 6: Accidental release measures**

## · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep people at a distance and stay on the windward side.

Ensure adequate ventilation

Keep away from ignition sources.

Avoid contact with the eyes and skin.

## · 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Keep contaminated washing water and dispose of appropriately.

## · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

## · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

## · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with the eyes and skin.

Avoid breathing vapours.

Do not eat, drink, smoke or sniff while working.

Ensure that washing facilities are available at the work place.

## · Information about fire - and explosion protection:

Highly flammable.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

Use explosion-proof apparatus / fittings and spark-proof tools.

### · 7.2 Conditions for safe storage, including any incompatibilities

Storage:

### · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

## · Information about storage in one common storage facility:

Store away from oxidising agents.

Protect from heat and direct sunlight.

## · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage temperature: +5 °C to +25 °C

· 7.3 Specific end use(s) No further relevant information available.

GF



Printing date 29.06.2017 Version number 4 Revision: 27.06.2017

**Trade name: TREMCO AW421** 

(Contd. of page 4)

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:
108-88-3 toluene

100-00-3 toluene

Short-term value: 384 mg/m<sup>3</sup>, 100 ppm Long-term value: 191 mg/m<sup>3</sup>, 50 ppm

Sk

### 78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm

Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

## · Ingredients with biological limit values:

### 78-93-3 butanone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

#### · Additional information:

The lists valid during the making were used as basis.

HSE EH40/2005 Workplace Exposure Limits (as amended)

### · 8.2 Exposure controls

### · Personal protective equipment:

## · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Do not eat, drink, smoke or sniff while working.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not breathe vapour.

Avoid contact with the eyes and skin.

Use skin protection cream for skin protection.

Pregnant women should strictly avoid inhalation or skin contact.

## · Respiratory protection:

Use only in well-ventilated areas.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

## · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

### · Material of gloves

Nitrile rubber, NBR

(Contd. on page 6)



Printing date 29.06.2017 Version number 4 Revision: 27.06.2017

**Trade name: TREMCO AW421** 

(Contd. of page 5)

#### EN 374

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

**EN 166** 

· Body protection: Protective work clothing

## **SECTION 9: Physical and chemical properties**

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Colour: Colourless

· Odour: Like aromatic solvents

· Initial boiling point and boiling range: 110 °C

· Solubility in / Miscibility with

water: Slightly soluble.

· Viscosity:

Dynamic at 20 °C: <50 cP

· Solvent content:

**VOC (EU)** 100 % **VOC (EC)** 850 g/l

• 9.2 Other information No further relevant information available.

## **SECTION 10: Stability and reactivity**

· 10.1 Reactivity Stable

(Contd. on page 7)



Printing date 29.06.2017 Version number 4 Revision: 27.06.2017

**Trade name: TREMCO AW421** 

(Contd. of page 6)

- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Reacts with strong oxidising agents.

Reacts with reducing agents.

· 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
108-88-3 toluene			
Oral	LD50	6000 mg/kg (rat)	
Dermal	LD50	6000 mg/kg (rabbit)	
Inhalative	LC50/4 h	21 mg/L (rat)	

- Primary irritant effect:
- · Skin corrosion/irritation

Irritant to skin and mucous membranes.

Strong degreasing effect.

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Harmful: may cause lung damage if swallowed.

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

CAS 108-88-3; Repr. 2 (CLP)

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

· STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

GB



Printing date 29.06.2017 Version number 4 Revision: 27.06.2017

**Trade name: TREMCO AW421** 

(Contd. of page 7)

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity:

### 108-88-3 toluene

LC50/96 h 24 mg/L (rainbow trout)

13 mg/L (carassius auratus)

EC50/48 h 11.5 mg/L (daphnia magna)

- 12.2 Persistence and degradability The product is not easily, but potentially biodegradable.
- · 12.3 Bioaccumulative potential Does not accumulate in organisms
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:

#### 108-88-3 toluene

IC50/72 h 12 mg/L (selenstrum capricornutum)

- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- Recommendation

Disposal must be made according to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Waste disposal key: UK (WM3): HP3 HP4 HP5 HP10
- · European waste catalogue

14 06 03\* other solvents and solvent mixtures

- · Uncleaned packaging:
- · Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

Non contaminated packagings may be recycled.

## **SECTION 14: Transport information**

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1993
- · 14.2 UN proper shipping name
- · ADR 1993 FLAMMABLE LIQUID, N.O.S. (TOLUENE)

(Contd. on page 9)



Printing date 29.06.2017 Version number 4 Revision: 27.06.2017

	(Contd. of page 8)
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (TOLUENE)
· 14.3 Transport hazard class(es)	
· ADR	
· Class · Label	3 (F1) Flammable liquids.
· IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	II
<ul><li>· 14.5 Environmental hazards:</li><li>· Marine pollutant:</li></ul>	No
<ul> <li>14.6 Special precautions for user</li> <li>Danger code (Kemler):</li> <li>EMS Number:</li> <li>Stowage Category</li> </ul>	Warning: Flammable liquids. 33 F-E, <u>S-E</u> B
<ul> <li>14.7 Transport in bulk according to Annex II o Marpol and the IBC Code</li> </ul>	f Not applicable.
· Transport/Additional information:	
ADR     Limited quantities (LQ)     Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<ul><li>Transport category</li><li>Tunnel restriction code</li></ul>	2 D/E
· IMDG     · Limited quantities (LQ)     · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (TOLUENE), 3, II



Printing date 29.06.2017 Version number 4 Revision: 27.06.2017

**Trade name: TREMCO AW421** 

(Contd. of page 9)

## **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

"CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments). COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

HSE EH40/2005 Workplace Exposure Limits (as amended)

- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

· \* Data compared to the previous version altered.