

**PINK GRIP SOLVENT FREE BUT ITS WHITE**

| Colour | Product Code | Pack Size | Box Qty |
|--------|--------------|-----------|---------|
| WHITE  | PINKWE       | C4        | 12      |

**Product Description**

EVERBUILD PINK GRIP SOLVENT FREE BUT ITS WHITE is a direct bond solvent free gap filling adhesive specifically formulated for the professional user. The product can be used to replace mechanical fixings in a wide variety of home improvement applications. Ideal for bonding wood, brick, plaster, plasterboard, polystyrene, metals and plastics.

**Benefits**

- Solvent free - environmentally friendly formulation
- Excellent adhesion/bond strength - adheres to most common surfaces.
- Enhanced slump resistance for quick simple direct bonding without the need for temporary support in many applications.
- Good “nip off” quality to prevent messy stringing of adhesive.
- High solids formulation - excellent gap filling properties without shrinkage.
- Extended open time - allows for easy repositioning after fixing.
- Will adhere to damp surfaces.
- Water clean up - no hazardous solvents.

**Areas For Use**

- Bonding dado rails, architrave's and skirting .
- Fixing wall cladding direct to internal wall surfaces or timber battens.
- Fixing battens directly onto walls without fastenings.
- Bonding carpet gripper systems to most floors without the need for nails or tacks.
- Bonding stair nosing to concrete or wooden stairs.
- Securing aluminium or other skin panels to the framework or portable industrial buildings and caravans.

**Limitations**

- Do not in situations where both surfaces are non -porous (ed plastic/plastic - metal/metal) - use PINK GRIP
- Do not use as a mirror adhesive: use EVERBUILD MIRROR MATE
- Caution : External use: The product will cure at a dramatically slower rate when used externally. For this reason, we recommend EVERBUILD PINK GRIP for external applications (solvent based product).

### Surface Preparation

The surfaces to be glued should be clean and free from dust, grease and other contaminants. Wood, plaster and brick may be damp but not running wet. Use mechanical abrasion to clean porous surfaces if necessary before application.

### Application

Apply PINK GRIP SF BUT ITS WHITE to one side either in strips or daubs. (or by trowel for low viscosity grade). Position the object to be fixed, then move from side to side and simultaneously apply pressure to achieve an even bond. If the object is wrongly positioned, slide it to the correct position. Finally, apply maximum pressure for a short time. (up to 1 minute) Wipe away any excess with a damp cloth making a neat joint between the two bonded surfaces. Temporary mechanical fixings may be required for heavy objects while full bond strength is reached.

### Specific Data

|                         |   |
|-------------------------|---|
| <b>Form</b>             | White thixotropic paste (ready to use)  |
| <b>Viscosity</b>        | 250,000-450,000cps (Brookfield S70 Spindle)   |
| <b>Coverage</b>         | 1.5 x 400ml cartridges per m <sup>2</sup>   |
| <b>Solids</b>           | 75-80%  |
| <b>Final Cure</b>       | 24 -48 hours depending on substrates  |
| <b>Specific Gravity</b> | 1.25 – 1.35   |
| <b>Flash Point</b>      | None (solvent free)   |
| <b>Open Time</b>        | Max 10 mins at 23°C and 50% R.H   |
| <b>Application Temp</b> | +4 to +35°C   |
| <b>Service Temp</b>     | -10 to +70°C  |
| <b>Durability</b>       | Up to 15 years when used as recommended   |
| <b>Compatibility</b>    | Can be used in contact with most building materials but should not be used against bituminous compounds or mirror backings. |

### Health & Safety

Consult MSDS for full list of hazards.

### Storage

Store in original unopened containers between 15 and 20°C

### Shelf Life

24 months from date of manufacture.

*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*