

## 360FC FAST CURE PUR WOOD GLUE D4

### Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/5/2016

Revision date:

Supersedes:

Version: 0.0

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product form : Mixture  
Trade name : 360FC FAST CURE PUR WOOD GLUE D4  
Product code : 360FC  
Type of product : Adhesives  
Product group : Trade product

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### 1.2.1. Relevant identified uses

Intended for general public

###### 1.2.2. Uses advised against

No additional information available

##### 1.3. Details of the supplier of the safety data sheet

AKKİM YAPI KİMYASALLARI SANAYİ ve TİCARET A.Ş.  
Yeşilbayır mahallesi Şimşir sokak No:22  
34555 İSTANBUL - TURKEY  
T +90 2127711371 - F +90 2127713888  
[info@akfix.com](mailto:info@akfix.com) - [www.akfix.com](http://www.akfix.com)

##### 1.4. Emergency telephone number

Emergency number : +90 2127711371 (9:00 am - 17:00 pm GMT+2)

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours)	

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixture/Su

Sensitisation — Respiratory, Category 1 H334 Calculation method  
Sensitisation — Skin, Category 1 H317 Calculation method  
Carcinogenicity, Category 2 H351 Calculation method

Full text of hazard classes and H-statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Suspected of causing cancer. May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

##### 2.2. Label elements

###### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS08

Signal word (CLP) : Danger

Hazardous ingredients : 4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate; benzoyl chloride

Hazard statements (CLP) : H317 - May cause an allergic skin reaction  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled  
H351 - Suspected of causing cancer

Precautionary statements (CLP) : P261 - Avoid breathing fume, gas, mist, vapours



# 360FC FAST CURE PUR WOOD GLUE D4

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/5/2016

Revision date:

Supersedes:

Version: 0.0

P280 - Wear protective clothing, protective gloves, face protection  
P284 - [In case of inadequate ventilation] wear respiratory protection  
P302+P352 - IF ON SKIN: Wash with plenty of water  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P342+P311 - If experiencing respiratory symptoms: Call a doctor, a POISON CENTER  
P405 - Store locked up  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate (Note C)(Note 2)	(CAS No) 101-68-8 (EC no) 202-966-0 (EC index no) 615-005-00-9 (REACH-no) 01-211945701447-0000	2.5 - 4.5	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
benzoyl chloride	(CAS No) 98-88-4 (EC no) 202-710-8 (EC index no) 607-012-00-0	0.05 - 0.1	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Skin Sens. 1, H317

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate	(CAS No) 101-68-8 (EC no) 202-966-0 (EC index no) 615-005-00-9 (REACH-no) 01-211945701447-0000	(C >= 0.1) Resp. Sens. 1, H334 (C >= 5) Eye Irrit. 2, H319 (C >= 5) Skin Irrit. 2, H315 (C >= 5) STOT SE 3, H335

Note 2 : The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/injuries after skin contact	: May cause an allergic skin reaction.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## 360FC FAST CURE PUR WOOD GLUE D4 Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/5/2016

Revision date:

Supersedes:

Version: 0.0

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

360FC FAST CURE PUR WOOD GLUE D4		
Austria	Local name	Diphenylmethan-4,4'-diisocyanat
Austria	MAK (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Austria	MAK (ppm)	0.005 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
Austria	MAK Short time value (ppm)	0.01 ppm
Austria	Remark (AT)	Sah
Belgium	Local name	4,4'-Diisocyanate de diphenylmethane (MDI)
Belgium	Limit value (mg/m <sup>3</sup> )	0.052 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	0.005 ppm
Czech Republic	Local name	Difenylmethan-4,4'-diisokyanát
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>

## 360FC FAST CURE PUR WOOD GLUE D4 Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/5/2016

Revision date:

Supersedes:

Version: 0.0

Czech Republic	Expoziční limity (PEL) (ppm)	0.005 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (NPK-P) (ppm)	0.01 ppm
Czech Republic	Remark (CZ)	S
Denmark	Local name	Diphenylmethan-4,4'-diisocyanat
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	0.005 ppm
Estonia	Local name	4,4'-metüleendifenüül-diisotsüanaat (fenüülisotsüanaat)
Estonia	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Estonia	OEL TWA (ppm)	0.005 ppm
Estonia	OEL STEL (ppm)	0.1 ppm
France	Local name	4,4'-Diisocyanate de diphenylmethane (3)
France	VME (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
France	VME (ppm)	0.01 ppm
France	VLE (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup>
France	VLE (ppm)	0.02 ppm
Germany	Local name	4,4'-Methylendiphenyl-diisocyanat
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Germany	Remark (TRGS 900)	DFG, 11, 12, Sa, Y
Greece	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	0.02 ppm
Greece	OEL STEL (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup>
Greece	OEL STEL (ppm)	0.02 ppm
Hungary	Local name	difenilmetán-4,4'-diizocianát (MDI)
Hungary	AK-érték	0.05 mg/m <sup>3</sup>
Hungary	CK-érték	0.05 mg/m <sup>3</sup>
Hungary	Megjegyzések (HU)	i, sz; I.
Ireland	Local name	4,4'-Methylene-diphenyl diisocyanate (as —NCO)
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	0.02 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	0.07 mg/m <sup>3</sup>
Ireland	Notes (IE)	Sen
Lithuania	Local name	Metileno bisfenilizocianatas (MDI)
Lithuania	IPRV (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	0.005 ppm
Lithuania	NRV (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
Lithuania	NRV (ppm)	0.01 ppm
Lithuania	Remark (LT)	J
Poland	Local name	Metylenobis(fenylizocyanian (diizocyanian 4,4'- metylenodifenylu)
Poland	NDS (mg/m <sup>3</sup> )	0.03 mg/m <sup>3</sup>
Poland	NDSch (mg/m <sup>3</sup> )	0.09 mg/m <sup>3</sup>
Portugal	Local name	Metilenodifenilisocianato (MDI)
Portugal	OEL TWA (ppm)	0.005 ppm
Slovenia	Local name	difenilmetan-4,4'-diizocianat (4,4'-metilendifenil diizocianat)
Slovenia	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Slovenia	OEL STEL (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Spain	Local name	Diisocianato de 4,4'-difenilmetano (MDI)
Spain	VLA-ED (mg/m <sup>3</sup> )	0.052 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	0.005 ppm
Spain	Notes	Sen (Sensibilizante. Véase Apartado 6.)
Sweden	Local name	4,4'-Methylenediphenyl diisocyanate
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	0.03 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	0.002 ppm
Sweden	takgränsvärde (TGV) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>

## 360FC FAST CURE PUR WOOD GLUE D4 Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/5/2016

Revision date:

Supersedes:

Version: 0.0

Sweden	takgränsvärde (TGV) (ppm)	0.005 ppm
Norway	Local name	Difenylmetan-4,4'-diisocyanat (MDI)
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Norway	Grenseverdier (AN) (ppm)	0.005 ppm
Norway	Merknader (NO)	A
Australia	Local name	Methylene bisphenyl isocyanate (MDI)
Australia	TWA (mg/m <sup>3</sup> )	0.02 mg/m <sup>3</sup>
Australia	STEL (mg/m <sup>3</sup> )	0.07 mg/m <sup>3</sup>
USA - ACGIH	Local name	Methylene bisphenyl isocyanate (MDI)
USA - ACGIH	ACGIH TWA (ppm)	0.01 ppm
USA - ACGIH	Remark (ACGIH)	Resp sens
<b>4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate (101-68-8)</b>		
Austria	Local name	Diphenylmethan-4,4'-diisocyanat
Austria	MAK (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Austria	MAK (ppm)	0.005 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
Austria	MAK Short time value (ppm)	0.01 ppm
Austria	Remark (AT)	Sah
Belgium	Local name	4,4'-Diisocyanate de diphenylmethane (MDI)
Belgium	Limit value (mg/m <sup>3</sup> )	0.052 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	0.005 ppm
Czech Republic	Local name	Difenylmethan-4,4'-diisocyanát
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (PEL) (ppm)	0.005 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (NPK-P) (ppm)	0.01 ppm
Czech Republic	Remark (CZ)	S
Denmark	Local name	Diphenylmethan-4,4'-diisocyanat
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	0.005 ppm
Estonia	Local name	4,4'-metüleendifenüül-diisotsüanaat (fenüülisotsüanaat)
Estonia	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Estonia	OEL TWA (ppm)	0.005 ppm
Estonia	OEL STEL (ppm)	0.1 ppm
France	Local name	4,4'-Diisocyanate de diphenylmethane (3)
France	VME (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
France	VME (ppm)	0.01 ppm
France	VLE (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup>
France	VLE (ppm)	0.02 ppm
Germany	Local name	4,4'-Methylenediphenyldiisocyanat
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Germany	Remark (TRGS 900)	DFG, 11, 12, Sa, Y
Greece	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	0.02 ppm
Greece	OEL STEL (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup>
Greece	OEL STEL (ppm)	0.02 ppm
Hungary	Local name	difenilmetán-4,4'-diizocianát (MDI)
Hungary	AK-érték	0.05 mg/m <sup>3</sup>
Hungary	CK-érték	0.05 mg/m <sup>3</sup>
Hungary	Megjegyzések (HU)	i, sz; I.
Ireland	Local name	4,4'-Methylene-diphenyl diisocyanate (as —NCO)
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	0.02 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	0.07 mg/m <sup>3</sup>
Ireland	Notes (IE)	Sen
Lithuania	Local name	Metileno bisfenilizocianatas (MDI)
Lithuania	IPRV (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>

## 360FC FAST CURE PUR WOOD GLUE D4 Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/5/2016

Revision date:

Supersedes:

Version: 0.0

Lithuania	IPRV (ppm)	0.005 ppm
Lithuania	NRV (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
Lithuania	NRV (ppm)	0.01 ppm
Lithuania	Remark (LT)	J
Poland	Local name	Metylenobis(fenylizocyanian (diizocyanian 4,4'-metylenodifenylu)
Poland	NDS (mg/m <sup>3</sup> )	0.03 mg/m <sup>3</sup>
Poland	NDSch (mg/m <sup>3</sup> )	0.09 mg/m <sup>3</sup>
Portugal	Local name	Metilendifenilisocianato (MDI)
Portugal	OEL TWA (ppm)	0.005 ppm
Slovenia	Local name	difenilmetan-4,4'-diizocianat (4,4'-metilendifenil diizocianat)
Slovenia	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Slovenia	OEL STEL (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Spain	Local name	Diisocianato de 4,4'-difenilmetano (MDI)
Spain	VLA-ED (mg/m <sup>3</sup> )	0.052 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	0.005 ppm
Spain	Notes	Sen (Sensibilizante. Véase Apartado 6.)
Sweden	Local name	4,4'-Methylenediphenyl diisocyanate
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	0.03 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	0.002 ppm
Sweden	takgränsvärde (TGV) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Sweden	takgränsvärde (TGV) (ppm)	0.005 ppm
Norway	Local name	Difenylnmetan-4,4-diisocyanat (MDI)
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Norway	Grenseverdier (AN) (ppm)	0.005 ppm
Norway	Merknader (NO)	A
Australia	Local name	Methylene bisphenyl isocyanate (MDI)
Australia	TWA (mg/m <sup>3</sup> )	0.02 mg/m <sup>3</sup>
Australia	STEL (mg/m <sup>3</sup> )	0.07 mg/m <sup>3</sup>
USA - ACGIH	Local name	Methylene bisphenyl isocyanate (MDI)
USA - ACGIH	ACGIH TWA (ppm)	0.01 ppm
USA - ACGIH	Remark (ACGIH)	Resp sens

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: Wear respiratory protection
Environmental exposure controls	: Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Light brown.
Odour	: Characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: Not applicable

## 360FC FAST CURE PUR WOOD GLUE D4 Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/5/2016

Revision date:

Supersedes:

Version: 0.0

Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 100 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.05 - 1.15 g/ml
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 5000 - 15000 cP
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content : < 50 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

Reproductive toxicity	: Not classified
-----------------------	------------------

Specific target organ toxicity (single exposure)	: Not classified
--	------------------

Specific target organ toxicity (repeated exposure)	: Not classified
--	------------------

Aspiration hazard	: Not classified
-------------------	------------------





# 360FC FAST CURE PUR WOOD GLUE D4

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/5/2016

Revision date:

Supersedes:

Version: 0.0

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

UN-No. (ADR) : Not applicable  
UN-No. (IMDG) : Not applicable  
UN-No. (IATA) : Not applicable  
UN-No. (ADN) : Not applicable  
UN-No. (RID) : Not applicable

#### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not applicable  
Proper Shipping Name (IMDG) : Not applicable  
Proper Shipping Name (IATA) : Not applicable  
Proper Shipping Name (ADN) : Not applicable  
Proper Shipping Name (RID) : Not applicable

#### 14.3. Transport hazard class(es)

##### ADR

Transport hazard class(es) (ADR) : Not applicable

##### IMDG

Transport hazard class(es) (IMDG) : Not applicable

##### IATA

Transport hazard class(es) (IATA) : Not applicable

##### ADN

Transport hazard class(es) (ADN) : Not applicable

##### RID

Transport hazard class(es) (RID) : Not applicable

#### 14.4. Packing group

Packing group (ADR) : Not applicable



## 360FC FAST CURE PUR WOOD GLUE D4 Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/5/2016

Revision date:

Supersedes:

Version: 0.0

Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable
Packing group (ADN)	: Not applicable
Packing group (RID)	: Not applicable

### 14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

### 14.6. Special precautions for user

#### - Overland transport

Not applicable

#### - Transport by sea

Not applicable

#### - Air transport

Not applicable

#### - Inland waterway transport

Not applicable

#### - Rail transport

Not applicable

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : < 50 g/l

#### 15.1.2. National regulations

##### Germany

VwVwS Annex reference : Water hazard class (WGK) 1, low hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

## 360FC FAST CURE PUR WOOD GLUE D4 Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/5/2016

Revision date:

Supersedes:

Version: 0.0

### Denmark

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product  
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Resp. Sens. 1	Sensitisation — Respiratory, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

### SDS EU AKFIX

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*